

# 8X Slim slot-in DVD Multi Writer: AD-7673S Labelflash

- Read speed: 8x max. DVD and 24x max. CD
- Write speed:
 

DVD-R:	8x max.	DVD+R:	8x max.
DVD-R DL:	6x max.	DVD+R9:	6x max.
DVD-RW:	6x max.	DVD+RW:	8x max.
DVD-RAM:	5x max.		
CD-R:	24x max.	CD-RW:	24x max.
- Slot in DVD/CD media load
- S-ATA interface  
(max. 150 MByte/sec transfer rate)
- Anti “buffer under run error” system
- 0.16 kg weight
- Labelflash™- Write labels with a laser!



Specifications	8x slim S-ATA slot-in DVD Multi Writer (AD-7673S)	
	DVD	CD
Transfer Rate read (max.)	8x CAV (max. 11000 kByte/s)	24x CAV (max. 3600 kByte/s)
Transfer Rate write	8x CAV (max. 11000 kByte/s)	24x CAV (max. 3600 kByte/s)
-R	8x CAV (max. 11000 kByte/s)	/
-R DL	6x ZCLV (max. 8250 kByte/s)	/
-RW	6x ZCLV (max. 8250 kByte/s)	24x ZCAV (max. 3600 kByte/s)
-RAM	5x ZCLV (max. 6900 kByte/s)	/
+R	8x ZCLV (max. 11000 kByte/s)	/
+R9	6x ZCLV (max. 8250 kByte/s)	/
+RW	8x ZCLV (max. 11000 kByte/s)	/
Access Time	180 ms	150 ms
Mechanism	Slot-in	
Interface	S-ATA	
Burst Transfer Rate	1.5 Gbps	
Cache Memory	2 MByte	
Media/Modes supported	DVD-ROM, DVD-R(DL), DVD-RW, DVD+R(9), DVD+RW, DVD-Video, CD-ROM, CD-ROM XA, CD-Audio, CD Extra, CD Text, CD-I Ready, CD-Bridge, Photo-CD, VideoCD, Hybrid CD	
Writing methods	DAO (disc at once), SAO (session at once), TAO (track at once) with zero gap, variable or fixed packet, multisession	
Compatibility	MultiRead, PC2001, Windows Vista™ compatible, Labelflash™	
Weight	0.16 kg	
Dimensions	129mm x 12.7mm x 129mm	

